



Instructions for the safe use of: Power Operated Blocks

The information in this leaflet should be passed to the user of the equipment

This document is issued in accordance with the requirements of Section 6 of the Health and Safety at Work etc Act 1974, amended March 1988. It outlines the care and safe use of POWER OPERATED BLOCKS and is based on Section 5 of the LEEA Code of Practice for the Safe Use of Lifting Equipment.* It should be read in conjunction with the requirements for lifting appliances for general purposes, given overleaf, which form an integral part of these instructions.

This information is of a general nature only covering the main points for the safe use of power operated blocks. It may be necessary to supplement this information for specific applications.

ALWAYS:

- Store and handle power operated blocks correctly.
- Inspect the block and accessories before use and before placing into storage.
- For top hook suspension, use hooks that are fitted with safety catches or mouse the hook and ensure the support fits freely into the seat of the hook.
- For trolley suspension, ensure the trolley is correctly set for the beam width.
- Check that the bottom hook will reach its lowest point without running the chain or rope fully out.
- Raise the load just clear then halt the lift to ensure the integrity of the block before continuing with the lift. If the block has more than one speed, start in the slow speed.

NEVER:

- Expose power operated blocks to chemicals, particularly acids, without consulting the supplier.
- Expose power operated blocks directly to the elements, water spray, steam etc without consulting the supplier.
- Replace the load chain or rope with a longer one without consulting the supplier.
- Use the load chain or rope to form a sling.
- Change motions without first allowing the motor to stop.
- Allow persons to ride on power operated blocks.

Selecting the Correct Block

Power operated blocks are available in a range of capacities, designs and suspensions with electric or pneumatic power options. Select the block to be used and plan the lift taking the following into account:

Type of block - chain, wire rope - electric, pneumatic - class of use - capacity and range of lift etc.

Type of suspension - hook, trolley, fixed.

Speeds and control - single speed, dual speed - pendant push button, pull cord, remote etc.

Power operated blocks are designed for vertical lifting only.

Consult the supplier if the block is to be used in areas of high risk, exposed to the elements, water, steam etc, with hazardous substances, eg acids** or chemicals, or subjected to extremes of temperature.

Storing and Handling Power Operated Blocks

Never return damaged blocks to storage. They should be dry, clean and protected from corrosion.

In the case of blocks used for temporary applications, store them on a purpose made rack or suspended from their top suspension fitting. Trailing cables, pendants etc may be

removed, identified and stored separately to prevent loss or damage whilst in store.

In the case of blocks left in situ, park the block in a suitable position so that it is protected from damage and does not present a danger. Raise the bottom hook so that it is not a danger to persons or liable to become accidentally engaged. Isolate the power supply.

Installing and Commissioning

Follow the specific instructions for installation and commissioning issued by the supplier and the general requirements given overleaf. Ensure the controls work in the correct direction and that motion limits are set and operate correctly. If the block fails to operate correctly contact the supplier.

Using Power Operated Blocks Safely

Do not use defective blocks, slings or accessories.

Check the slinging arrangement, that the block is safely rigged, that the chain or rope is not twisted and that the load is free to move.

Raise the load just clear, halt the lift to ensure the integrity of the block, slinging arrangement etc. Always commence lifting in the slow speed. Avoid unnecessary inching of the load.

Check the travel path is clear and that you have a clear view so as to avoid accidental hook engagement or collision. Follow any particular site safety rules applicable to the movement of suspended loads.

Keep fingers, toes etc clear when lowering loads.

In-service Inspection and Maintenance

Follow the specific instructions for maintenance issued by the supplier. These should be incorporated into the site maintenance programme observing any particular needs due to the site or working conditions.

Regularly inspect the block and, in the event of the following defects, refer the block to a Competent Person for thorough examination: operational faults; block will not lift; slips back; motion commands reversed; over-runs when command released; wear; damage to trolley, hooks and fittings; damaged, worn or corroded chain or rope; other visible defects.

© Lifting Equipment Engineers Association 2004 SI No. 14.2

Further information is given in:

** HSE Guidance Note PM39 - Hydrogen Embrittlement of Grade T Chain

* The Code of Practice for the Safe Use of Lifting Equipment, published by:

LIFTING EQUIPMENT ENGINEERS ASSOCIATION



Waggoners Court, 77 The Street, Manuden,
Bishop's Stortford, Herts. CM23 1DW
United Kingdom
Tel: + 44 (0) 1279 816504
Fax: + 44 (0) 1279 816524
E-mail: mail@leea.co.uk

EUROPEAN MANAGEMENT & MARINE
CORPORATION

HOWE MOSS PLACE

KIRKILL INDUSTRIAL ESTATE DYCE

ABERDEEN AB21 0GS

T: + 44 1224 77 51 51

www . emmcorp . com

LIFTING APPLIANCES FOR GENERAL PURPOSES

(MANUAL AND POWER OPERATED BLOCKS)

The following information is based on Section 1 - Appendix 1.6 of the Code of Practice for the Safe Use of Lifting Equipment* and should be read in conjunction with the instructions for safe use, given overleaf, of which it forms an integral part and with any specific instructions issued by the supplier.

This information is of a general nature only covering the main points for the safe use of manual and power operated blocks.

ALWAYS:

- Ensure suspension points and anchorages are adequate for the full imposed load.
- Check the load chain/wire rope is hanging freely and is not twisted or knotted.
- Position the hook over the centre of gravity of the load.
- Check the operation of the brake before making the lift.
- Ensure the slings are secure and load is free to be lifted.
- Check the travel path is clear.
- Ensure the landing area is properly prepared.

NEVER:

- Exceed the marked SWL.
- Use the load chain/wire rope as a sling.
- Shock load the block or other equipment.
- Lift on the point of the hook.
- Overcrowd the hook with fittings.
- Permit the load to swing out of control.
- Leave suspended loads unattended.

Types of blocks

A wide range of manual and power operated blocks is available. This section of the leaflet is concerned with matters which are common to the safe use of the following listed equipment when used to lift in a vertical plane only.

Pulley blocks for fibre or wire rope used with winches, hand chain blocks, chain lever hoists, power operated wire rope blocks and power operated chain blocks. The use of trolleys is often associated with blocks and these may be built in with the trolley as an integral part of the appliance, or independent with the block hung on.

Operative Training

Lifting appliances should only be used by trained operatives** who understand their use and that of the associated equipment used in the lift.

Installation and Commissioning

The erection procedure will vary with the equipment and should be carried out in accordance with the suppliers instructions paying attention to the following matters:

Prior to installation inspect the equipment to ensure no damage has occurred in store or transit.

Ensure the support structure is adequate for the full loads that will be imposed, is tested and marked with the SWL.

When erecting trolleys ensure they are correctly set for the beam width and that the track is fitted with end stops and remains level at all loads up to the maximum.

When suspending appliances by a top hook ensure the support fits freely into the seat of the hook.

After erection ensure that the chain/wire rope hangs freely and is not twisted or knotted.

With power operated blocks the supply should be connected by a suitably Qualified Person taking account of any statutory or technical requirements (eg Electricity at Work Regulations, Pressure Systems and Transportable Gas Containers Regulations).

Test run to ensure the free and correct movement of the chain/rope. Check the operation of the brake. Check direction of control command, position and operation of travel limits and safety devices.

Safe Use of Blocks

The basic objectives of any lifting operation are to move the load to the desired location and land it safely, efficiently and without damage to the load, the equipment used or the surrounding buildings, plant etc. In addition to any specific instructions relating to the block the following general points must be observed:

- o Never attempt lifting operations unless you have been trained in the use of the equipment and slinging procedures.
- o Position the hook directly over the centre of gravity so that the line of pull is vertical.
- o Do not use the chain/wire rope to sling the load, ie do not wrap it round the load, back hook or choke hitch.
- o Do not lift on the point of the hook or overcrowd the hook with fittings.
- o Never lift/lower more than the marked SWL. In the case of manual equipment if abnormally high effort is required, and with power operated appliances they fail to lift the load, or if the load slips this is an indication of too high a load or a fault - check the load and the appliance.
- o Avoid unnecessary inching of power operated appliances and do not impose sudden or shock loads.
- o Push rather than pull loads suspended from appliances with push/pull trolleys and if un-laden pull on the bottom hook. Never pull an appliance by the pendant control, supply cable or hose.
- o Avoid sudden movement of travel motion or undue effort in pushing the load which can cause the load to swing.
- o Avoid excessive or intentional use of motion limits unless they are additional limits intended for that purpose. Avoid running appliances against end stops.
- o Do not allow anyone to pass under or ride upon the load. Never leave suspended loads unattended unless in an emergency then ensure the area is cordoned off and kept clear.
- o Do not remove guards, protective covers, weather proof covers, heat shields etc without the authority of a Competent Person

In-Service Inspection and Maintenance

The Provision and Use of Work Equipment Regulations 1998 and the Lifting Operations and Lifting Equipment Regulations 1998 both require that lifting equipment properly maintained. This is an ongoing duty that falls on the user and a planned routine maintenance programme will be necessary.

In addition to the statutory thorough examinations by a Competent Person, regular in-service inspections should be made to find any faults and damage that might arise. If any are found they should be referred to the Competent Person.

The maintenance programme must meet the requirements of the manufacturers instructions and any special requirements due to the conditions of service. This may be combined with maintenance of other equipment used in association with the appliance, eg power feed system. Check the block and its associated equipment daily for obvious faults and signs of damage.

Further information is given in:

**LEEA Code of Practice for the Safe Use of Lifting Equipment*

***HSE Guidance Note GS39 - Training of Crane Drivers and Slingers*